

EP-1800 OPERATING INSTRUCTIONS

Safety Warnings

- ❖ Before using the EP-1800 please follow all safety precautions. (Ex: Safety Glasses, Gloves etc.)
- ❖ Inspect tool for worn or broken parts before operating.
- ❖ Only trained operators should use this tool.
- ❖ The EP-1800 is recommended for use with only (.015-.023) Steel Strap. Each tool is only made to work with one strap width. The EP-1800 is available for 3/8", 1/2", 5/8" and 3/4" steel strap.
- ❖ Watch fingers and keep them away from the front of the tool or by areas that can pinch or cut.
- ❖ Unsafe use of the EP-1800 may result in blindness, severe laceration, amputation or death.

Operating Instructions

1. Hold the EP-1800 vertically over the seal. Next, put the jaws of the tool over the center of the seal. Look closely to the seal's position. If the seal is crimped to the side and not centered, the strap may loosen and break apart. This may result in severe injury or death.
2. While still holding the tool vertically, pull the handles of the EP-1800 together. Once the handles cannot be pulled together any further the seal will then be complete.
3. Once the seal is completed, remove the EP-1800 to inspect the seal. The seal should be flat against the strapping, with the indentations on the center of the seal. Both pieces of strap should be going through the seal. If the seal is not crimped properly, remove and start over. **DO NOT USE THE SAME SEAL.** Trying to reseal a used seal will decrease the break strength and you will result in an improper seal.
4. Improper usage of the EP-1800 may result in damage to the tool and possibly cause serious injury or death. Damage to the EP-1800 will require repair or replacement at owner's expense.

